

H05VVC4V5-K (NYSLYCYÖ-JZ) flexible, number

coded, oil resistant, EMC-preferred type



A

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
13963	2 x 1	8,6	54,0	114,0	17
13084	3 G 1	9,3	64,0	142,0	17
13085	4 G 1	10,2	76,0	175,0	17
13086	5 G 1	11,0	89,0	205,0	17
13087	6 G 1	11,8	101,0	236,0	17
13088	7 G 1	12,9	114,0	264,0	17
13964	8 G 1	13,6	130,0	301,0	17
13089	9 G 1	14,4	144,0	335,0	17
13090	12 G 1	15,6	186,0	420,0	17
13965	14 G 1	15,7	198,0	433,0	17
13091	18 G 1	17,4	284,0	561,0	17
13966	19 G 1	17,4	307,0	584,0	17
13092	25 G 1	21,1	387,0	766,0	17
13967	27 G 1	21,9	410,0	822,0	17
13093	34 G 1	24,1	500,0	996,0	17
13968	36 G 1	23,8	511,0	1001,0	17
13969	37 G 1	25,1	523,0	1018,0	17
13131	41 G 1	26,0	578,0	1155,0	17
13094	50 G 1	28,5	681,0	1300,0	17
13095	61 G 1	30,1	710,0	1500,0	17
13970	65 G 1	32,4	769,0	1510,0	17
13971	2 x 1,5	9,1	64,0	146,0	16
13096	3 G 1,5	10,2	82,0	176,0	16
13097	4 G 1,5	10,9	99,0	207,0	16
13098	5 G 1,5	11,6	123,0	235,0	16
13099	6 G 1,5	12,4	125,0	279,0	16
13100	7 G 1,5	13,5	148,0	314,0	16
13972	8 G 1,5	15,6	172,0	345,0	16
13101	9 G 1,5	15,6	187,0	380,0	16
13102	12 G 1,5	16,8	274,0	500,0	16

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
13973	14 G 1,5	18,3	294,0	560,0	16
13103	18 G 1,5	20,0	386,0	707,0	16
13974	19 G 1,5	20,4	394,0	723,0	16
13104	25 G 1,5	24,2	531,0	950,0	16
13975	27 G 1,5	24,6	546,0	1014,0	16
13105	32 G 1,5	26,0	638,0	1133,0	16
13106	34 G 1,5	26,3	671,0	1204,0	16
13976	36 G 1,5	27,7	700,0	1261,0	16
13977	37 G 1,5	27,7	720,0	1300,0	16
13132	41 G 1,5	29,1	840,0	1453,0	16
13107	50 G 1,5	34,0	997,0	1663,0	16
13108	61 G 1,5	36,5	1120,0	1852,0	16
13978	65 G 1,5	38,1	1197,0	1971,0	16
13985	2 x 2,5	11,4	110,0	190,0	14
13109	3 G 2,5	11,7	148,0	243,0	14
13110	4 G 2,5	12,8	169,0	280,0	14
13111	5 G 2,5	13,9	220,0	342,0	14
13112	7 G 2,5	15,9	284,0	439,0	14
13979	8 G 2,5	18,7	314,0	489,0	14
13113	12 G 2,5	20,6	470,0	760,0	14
13980	14 G 2,5	22,5	504,0	890,0	14
13114	18 G 2,5	24,3	572,0	1052,0	14
13115	25 G 2,5	29,0	740,0	1375,0	14
13981	27 G 2,5	29,8	971,0	1507,0	14
13116	34 G 2,5	33,0	1179,0	1892,0	14
13982	36 G 2,5	33,3	1268,0	1998,0	14
13983	41 G 2,5	36,0	1473,0	2286,0	14
13117	50 G 2,5	38,5	1660,0	2673,0	14
13118	61 G 2,5	42,0	1992,0	3085,0	14

Dimensions and specifications may be changed without prior notice. (RA01)